

G Series Finishing Tools
Outils de Finition, Série "G"
Werkzeuge zur Oberflächenbearbeitung der Baureihe G
Herramientas de Acabado - Serie G
Utensili per la Finitura - Serie G



Straight grinders
 Meuleuses droites
 Gerade Schleifmaschinen
 Amoladoras rectas
 Smerigliatrici diritte

G1H350PG4M



G2H250PG4M



G2X180PH63



G3X180PG4M



**Standard
Equipment**




- Integral trigger safety lock.
- Levier de sécurité.
- Drücker-Sicherheitsarretierung.
- Palanca de seguridad.
- Leva di sicurezza con bloccaggio.

- Piped-away exhaust.
- Gaine d'échappement.
- Abluft-Ableitsatz.
- Juego escape remoto.
- Tubo con scarico aria a distanza.




See burrs page 15 — Fraises carbure présentées en page 15 — Fräser siehe Seite 15 —
 Fresas carburo presentadas en página 15 — Per le frese al carburo, vedere pagina 15.

Erickson



Type 1



Specifications at 90 psi – Caractéristiques à 6,2 bar – Technische Daten bezogen auf 6,2 bar – Especificaciones a 6,2 bar – Caratteristiche a 6,2 bar

Ref.	kWatt	1 min.						
	kW	rpm	mm	mm	kg	mm	in (NPT)	mm
STANDARD MODELS - MODÈLES STANDARDS - STANDARDMODELLE - MODELOS ESTÁNDAR - MODELLI STANDARD								
G1H200PG4M	0.30	20 000	Ø 6 Erickson	–	0.40	156	1/4	10
G1H250PG4M	0.30	25 000	Ø 6 Erickson	–	0.40	156	1/4	10
G1H250PH63	0.30	25 000	–	Ø 75 - Type 1	0.54	156	1/4	10
G1H350PG4M	0.30	35 000	Ø 6 Erickson	–	0.40	156	1/4	10
G2H180PG4M	0.60	18 000	Ø 6 Erickson	–	0.73	187	1/4	10
G2H200PG4M	0.60	20 000	Ø 6 Erickson	–	0.73	187	1/4	10
G2H250PG4M	0.60	25 000	Ø 6 Erickson	–	0.73	187	1/4	10
EXTENDED MODELS - MODÈLES LONGS - VERLÄNGERTE MODELLE - MODELOS EXTENDIDAS - MODELLI PROLUNGATI								
G1X200PG4M	0.30	20 000	Ø 6 Erickson	–	0.60	232	1/4	10
G1X250PG4M	0.30	25 000	Ø 6 Erickson	–	0.60	232	1/4	10
G1X350PG4M	0.30	35 000	Ø 6 Erickson	–	0.60	232	1/4	10
G2S180PH63	0.60	18 000	–	Ø 75 - Type 1	1.10	219	1/4	10
G2X180PG4M	0.60	18 000	Ø 6 Erickson	–	1.20	308	1/4	10
G2X180PH63	0.60	18 000	–	Ø 75 - Type 1	1.45	314	1/4	10
G2X200PG4M	0.60	20 000	Ø 6 Erickson	–	1.20	308	1/4	10
G2X250PG4M	0.60	25 000	Ø 6 Erickson	–	1.20	308	1/4	10
G2XX180PG6M	0.60	18 000	Ø 8 Erickson (1)	–	1.30	315	1/4	10
G3X150PH64	1.00	15 000	–	Ø 100 - Type 1	2.00	359	3/8	13
G3X180PH63	1.00	18 000	–	Ø 75 - Type 1	2.00	359	3/8	13
G3X150PG4M	1.00	15 000	Ø 6 Erickson (1)	–	1.70	359	3/8	13
G3X180PG4M	1.00	18 000	Ø 6 Erickson (1)	–	1.70	359	3/8	13

(1) Double bearing — Double rangée de roulements — Doppellager — Doble fila de rodamientos — Doppio cuscinetto.